



国家高新技术企业 浙江省著名商标



High purity pumps



东正一直致力于技术革新
是您值得信赖的事业伙伴
**Donjoy has been committed to
technical innovation, is your trustworthy
business partner!**

目录册技术资料仅供参考，
东正保留更新和升级的权利，恕不另行通知！
Catalogue technical information only for reference.
Donjoy reserves the rights to update and upgrade
without prior notice.

法律声明：
目录样册版权归东正所有，
如有抄袭，必将追究其法律责任和经济赔偿。
东正已获得国家版权局书刊号。
东正诸多产品技术，都具有专利保护，
如有抄袭，必将追究法律责任和经济赔偿。

Legal statement:
Copyright of the catalogue belongs to Donjoy.
If there is plagiarism, it will be investigated for legal
responsibility and economic compensation.
Donjoy has been granted publications number by
Chinese National Copyright.
Donjoy products and technology are with patent protection.
If there is plagiarism, it will be investigated for legal
responsibility and economic compensation.

温州空港新区总部生产基地

Wenzhou airport economic zone production base



占地面积约29000m²，总投资约1.2亿RMB，约2000万USD。

Covering an area of 29000 m², with total investment after construction is expected to 120 million yuan, about 20 million USD.

领先源于创新 创新源于专业

东正的专业与品质的邂逅源于创新的精神

东正创立于1993年，注册资本6088万(约1000万USD)，是一家专注于高精端PID阀门定位器，阀门控制单元，阀门位置反馈器、智能自控阀、比例调节阀、过程控制阀、高洁净泵、均质混合泵、清洗技术、压力容器和管道安全控制技术、高洁净管材和管道配件，集研发、生产与销售为一体的国家高新技术企业。产品用途涉及行业和领域有生物制药、食品饮料、酿酒、精细化工等工业领域。东正领先的技术和持续创新解决方案，对满足全球，尤其是新兴市场不断增长生物制药和食品饮料行业的需求起到了积极作用。

东正制造的产品母材料、加工技术、焊接技术、表面处理等技术指标均已达到国际领先水平。且符合ASME BPE、EHEDG、FDA、3A等一系列国际标准和规范要求。先后通过了由德国 TÜV 机构实施的欧盟承压设备指令(PED-97/23/EC)和(MD-06/42/EC)认证；美国 3A机构实施的3-A卫生标准认证；中国安全阀特种制造设备(TS)许可证和中国质量认证中心CQC ISO9001:2015 质量管理体系认证等多项国际权威认证。

东正凭借领先的技术、优异的品质和完善的售后服务体系，公司荣获为《国家高新技术企业》，《浙江省著名商标》、《科技型企业》、《创新型企业》、《专利示范企业》、《研发中心企业》，《守合同重信用AAA企业》等众多荣誉称号。





**Leading from innovation,
innovation from the professionalism!
Donjoy's professionalism and quality come from
the spirit of innovation!**

Donjoy was founded in 1993, with registered capital RMB 60.88 million (about 10million USD) We focus on developing high-precision PID valve positioner, Valve Control unit, Valve Position feedback device, intelligent automatic control valve, proportional valve, process control valve, high purity pump, homogeneous mixing pump, cleaning technology, pressure vessel, pipeline safety control technology, high clean pipe fitting&pipeline accessories and integrating r&d, production and sales as an integrated national high-tech enterprises. Donjoy's products are widely used in bio-pharmaceutical, food and beverage, wine, fine chemicals and other industrial fields. Donjoy's leading technology and innovation solutions meets growing demand in the industry of bio-pharmaceutical, food and beverage from the whole world, special emerging market.

Raw material, processing technology, welding technology, surface treatment and other technology from Donjoy have achieved advanced level in international market. It also complies with a series of international standards and specifications such as ASME BPE, EHEDG, FDA and 3A , It has passed the EU Pressure Equipment Directive (PED-97/23/EC) and (MD-06/42/EC) issued by the German TÜV organization; the 3-A health standard certification issued by the 3A organization; China Safety Valve Special Manufacturing Equipment (TS) License , China Quality Certification Center (CQC) and Quality Management System Certification (ISO9001:2015) and many other international authoritative certifications.

With advanced technology, excellent quality and perfect after-sales service system, Donjoy was awarded as National High-tech Enterprise, Provincial Famous Trademark, Science and Technology Enterprise, Innovative Enterprise, Patent Demonstration Enterprise, R & D Center Enterprise, AAA Credit Enterprise and many other honorary.





全面的创新技术能力
为您带来创造性的解决方案



Comprehensive innovation technology, capabilities Bring you creative solutions

东正拥有诸多领先的产品技术，如各种比例调节阀、过程自控阀、生物制药隔膜阀、防混双座阀、压力容器和管道安全控制技术、清洗技术、高洁净转子泵、螺杆泵、离心泵、自吸泵、均质乳化泵、均质混合泵、卫生管件和无菌管件等.....

Donjoy owes many leading technology products, such as various proportioning regulating valve, process automatic control valve, pharmaceutical diaphragm valve, mixed double seat valve, pressure vessel and pipeline safety control technology, clean technology, high cleanliness rotor pump, screw pump, centrifugal pump, self-priming pump, homogeneous emulsion pump, homogeneous mixing pump, sanitary fittings, aseptic pipe fittings and so on.



企业的成功源于创新。东正的成功基于创始人“开拓创新、追求卓越”的创新精神，1994年东正开发了第一只高洁净的蝶阀，这只蝶阀是东正的起始点。

控制器的研发成就完美的过程自动控制，2004年东正成功研发了技术领先的阀门定位器、阀门控制单元。

高洁净泵的研发确保物料输送的洁净，2006年东正成功研发了高精端的转子泵、离心泵、混合泵、自吸泵。

我们一直走在行业与时代的前沿，把不断革新的技术、日新月异的市场发展和客户需求作为自身最大的挑战。东正有自己的独立的思维和视野，始终保持领先致力于产品在新经济领域中的开发和应用。未来我们将一如既往的坚持以技术创新、以顾客为导向走向新的成功。

Success of an enterprise stems from innovation. Donjoy's success is based on the founder's innovative spirit of "pioneering innovation and pursuing excellence". In 1994, Donjoy developed the first highly purity butterfly valve, which was the starting point of Donjoy.

Research and development of the controller achieves perfect automatic process control. In 2004, Donjoy has successfully developed advanced valve positioner and valve control unit.

Research and development of high purity pump to ensure the purity of medium transportation. In 2006, Donjoy has successfully developed high precision lobe pump, centrifugal pump, mixing pump and self-priming pump.

We are always at the forefront of the industry and times, taking the continuous innovation of technology, rapid market development and customer demand as our biggest challenge. Donjoy has its own independent thought and horizons, and always maintains a leading position in the development and application of products in the new economic field. In future, we will continue to adhere to technological innovation and customer-oriented towards new success.



精益加工车间 Lean processing workshop



东正以科学技术领先为第一生产力，也是企业核心竞争力。只有不断投入核心技术研发和创新，不断追求卓越、精益求精、以先进生产设备，严格的质量管理体系，严谨的检测流程、保证每款产品的优良性能。

Donjoy takes leading in science and technology as the first productivity as well as the core competitiveness of the enterprise. With continuous investment in core technology research, development and innovation; constant pursuit of prominence and, excellence; advanced production equipment; strict quality management system; and rigorous testing process, we ensure excellent quality and performance of every product.



机器人生产线 Robot production line

装配车间 Assembly workshop



荣誉与资质

Honor and qualification

	<p>3A</p> <p>东正是美国3A认证组织的成员，3A是一个自愿组织，致力于维护公共卫生和乳制品产品质量通过独特的行业监管程序的设备，用于处理乳制品的卫生标准3-A。</p> <p>Donjoy is a member of US 3A Certification Organization, 3A is a voluntary organization dedicated to maintaining the quality of public health and dairy products through a unique industry regulatory process for the treatment of dairy product hygiene standards 3-A.</p> <ul style="list-style-type: none">◆ 54-02 (Diaphragm-Type Valves) NUMBER: 1580-隔膜阀◆ 02-11 (Centrifugal and Positive Rotary Pumps) NUMBER: 1579-离心泵◆ 85-03 (Double-Seal Mixproof Valves) NUMBER: 1787-双座防混阀◆ 64-00 (Pressure Reducing and Back Pressure Regulating Valves) NUMBER: 1784-恒压阀&调节阀◆ 53-06 (Compression-Type Valves) NUMBER: 1782-单座阀(换向阀)◆ 68-00 (Ball-Type Valves) NUMBER: 1785-蝶阀◆ 55-02 (Boot Seal-Type Valves) NUMBER: 1783-无菌取样阀◆ 84-02 (Personnel Access Ports for Wet Applications) NUMBER: 1786-人孔◆ 63-03 (Sanitary Fittings) NUMBER: 1581-卫生管件
	<p>PED/97/23/EC&MD/06/42/EC</p> <p>由德国TUV机构实施的欧盟承压设备安全指令 (PED-97/23/EC)。机械安全指令MD-06/42/EC。</p> <p>EU Pressure Equipment Safety Directive (PED-97/23/EC), Machinery Safety Directive MD-06/42/EC, implemented by TÜV, Germany.</p> <p>◆ MD/06/42/EC NUMBER: 705201402401-00 - LOBE PUMP转子泵 ◆ MD/06/42/EC NUMBER: 705201616101-00 - Centrifugal pump 离心泵 ◆ PED/97/23/EC NUMBER: DGR - 0036-QS-1153-14-Valves 阀门系列</p>
	<p>安全阀特种制造许可证(TS) Safety valve special manufacturing license</p> <p>东正通过了安全阀特种设备制造许可证，目前是国内首家通过“高洁净安全阀特种制造许可证”的企业(安全附件及安全保护装置)。</p> <p>◆其证书编号：TSF 733008-2019</p> <p>Donjoy has passed the safety valve special equipment manufacturing license. Recently, is the first enterprise in China to pass the "Special Manufacturing License for High Clean Safety Valves" (safety accessories and safety protection devices). ◆ Certificate number: TSF 733008-2019</p>
	<p>FDA.177.2600</p> <p>东正制造的高洁净阀门和泵以及液体设备等，与塑料接触密封圈全部通过或符合美国食品和药品管理局和联邦法规第21条即，CRF 21 FDA177.2600和FDA177.1550认证。其材质：EPDM VITON (FPM) SILICON HNBR 等橡胶和PTFE 塑料材料。 ◆符合美国 3-A-18-03-CLASS - II</p> <p>The seals of Donjoy's high-clearing valves, pumps and fluid equipment that contact with material, all pass or comply with the US Food and Drug Administration and Federal Regulations issue 21, i.e. CRF 21 FDA177.2600 and FDA177.1550 certification. The seals cover : EPDM, VITON (FPM), SILICON, HNBR and other rubber & PTFE plastic material. ◆ Meets US 3-A-18-03-CLASS - II</p>
	<p>ISO-9001-2015</p> <p>东正通过中国质量认证中心CCC,ISO9001-2015/GB/T19001-2015企业质量管理体系认证。 ◆其证书编号：00117Q38464R4M/3302.</p> <p>Donjoy passes the China Quality Certification Center CCC, ISO9001-2015/GB/T19001-2015 enterprise quality management system certification.</p> <p>◆ Its certificate number is 00117Q38464R4M/3302.</p>
	<p>卫生许可证 Hygiene License</p> <p>东正通过了省卫生厅卫生阀门，卫生管件等检验且获得了其颁发的证书。 ◆其批准文号：第0056号</p> <p>Donjoy passed the inspection of sanitary valves and sanitary fittings of the Provincial Health Department and obtained the certificate issued by it. ◆ Its approval number: No. 0056</p>
	<p>国家高新技术企业 National High-Tech Enterprise</p> <p>东正，经过20余年发展和技术研发，2011年被评定为国家高新技术企业。</p> <p>Donjoy, after more than 20 years of development and technology research & development, was assessed as a national high-tech enterprise in 2011.</p>
	<p>浙江省著名商标 Zhejiang province famous trademark</p> <p>东正，凭借先进的技术、优异的品质和完善的售后服务体系，2012年被浙江省工商局评定为浙江省著名商标。</p> <p>Donjoy, by virtue of advanced technology, excellent quality and perfect after-sales service system, was recognized as a famous trademark of Zhejiang Province by the Industrial and Commercial Bureau of Zhejiang Province in 2012.</p>

东正不但拥有以上认证和荣誉，且被评定为省科技型、创新型、专利示范、研发中心、重合同守信用等诸多荣誉。并拥有100多项专利技术。

Donjoy not only owes above certification and honors, but also has been evaluated as provincial science and technology type, innovation, patent demonstration, research and development center, contract keeping and other honors. It also owes more than 100 patented technologies.

荣誉与资质 Honor and qualification




东正不但拥有以上认证和荣誉，且被评定为省科技型、创新型、专利示范、研发中心、重合同守信用等诸多荣誉。并拥有100多项专利技术。

Donjoy not only owes above certification and honors, but also has been evaluated as provincial science and technology type, innovation, patent demonstration, research and development center, contract keeping and other honors. It also owes more than 100 patented technologies.




Centrifugal pump series

离心泵系列



工艺管道连接对泵使用的影响

The effect of pipe connections on pump usage



泵进口/出口连接管道的建议

液体在管道中会有能量的损失，分为沿程损失和局部阻力损失，这两种的损失最终会影响流量和扬程的损失。因此管道内部越光滑沿程损失越小，管径变化越小局部助力损失越小。因此尽可能不采用粗糙管道内壁和错误的连接方式，不要采用缩径过大、弯曲过多、弯曲过小等工艺管路。为了提高泵的使用寿命和泵的性能请尽量减少工艺管道弯曲和缩径等。(如图 (D-02)所示)

Suggestion for pump inlet / outlet connect to pipeline

Liquid in the pipeline will have energy loss, divided into along damage and local resistance damage, which will eventually affect the flow and head loss. Therefore, the smoother the inner part of the pipeline, the smaller the damage along the path; the smaller the diameter change, the smaller the local power loss. As a result, rough inner wall and connection should be avoided as much as possible. do not use the shrinkage diameter too large, too much bending, bending too small and so on process pipelines. In order to improve the service life of the pump and the performance of the pump, please try to reduce the process pipe bending and shrinkage diameter. (As shown in (D-02))

泵进口/出口连接距离的建议

为确保离心泵稳定运行并延长使用寿命，要求严格按照泵本体的进口和出口尺寸安装，严禁使用小于泵的进口和出口尺寸的管道连接，否则容易造成泵抖动、噪音、汽蚀余量增加等现象；泵进口连接管道需要保持一定直管距离；建议按照进口管道尺寸的5–10倍直径。(如图 (D-03) 所示)

Suggestions for pump inlet / outlet connection dimensions

In order to ensure the stable operation of the centrifugal pump and prolong the service life, it is required to install strictly according to the inlet and outlet sizes of the pump itself. It is strictly forbidden to use the pipe connection smaller than the inlet and outlet sizes of the pump, otherwise it will easily cause pump shake, noise, NPSH increase, etc.; the pump inlet connecting with pipeline needs to maintain a certain straight pipe distance; it is recommended to be 5–10 times the diameter of the inlet pipe. (As shown in (D-03))


泵电机和叶轮旋转方向

电机和叶轮的旋转方向是一致的，安装调试时要注意旋转方向，否则会产生流量和扬程不正常，长时间反向旋转，会导致机封损坏等情况。

Pump motor and impeller rotation direction

Rotation direction of motor and impeller is same. Pay attention to rotation direction when installation and debugging. Otherwise, the flow and head will be abnormal. Long-term reverse rotation will result in damage to mechanical seal.

工艺管道连接对泵使用的影响 The effect of pipe connections on pump usage



宽电压电机 Wide voltage motor

功率 Power(KW)	电压范围 Voltage	功率 Power(KW)	电压范围 Voltage
0.55	210~230V/50HZ	4.0~5.5	360V~400V/50HZ
0.75	360V~400V/50HZ	7.5~11	630V~690V/50HZ
1.1~1.5	420V~460V/60HZ	15~18.5	420V~460V/60HZ
2.2~3.0		22~30	

注意：电机采用 IEC EN IE2 能效等级，PTC热敏电阻。(相当于中国二级能效)

Note: The motor adopts IEC EN IE2 energy efficiency class, PTC thermistor. (Corresponding to China level two energy efficiency)

注意：其他电机功率、电压、频率等。请联系东正。

Note: Other motor power, voltage, frequency, etc., please contact DONJOY

O型圈配置 O-ring Configuration

我们所采用密封橡胶都符合FDA 177.2600; 3-A-18-03; Class II; USP Class VI Chapter 88 GB 4806.11; 等各种卫生高洁净的要求。

EPDM=标准

适用范围：温度 -10°C 到 130°C; PH值约 5~9, 可耐受各种卫生领域介质及工业化学品，成本低(推荐)。

FKM(Viton)=选项

适用范围：温度 -10°C 到 150°C; 可耐受各种卫生领域介质及工业化学品、油品等各种介质。

FFKM=选项

适用范围：温度 -30°C 到 250°C; 可耐受各种卫生领域介质及工业化学品、油品等各种介质，几乎可以涵盖所有介质，成本较高。

HNBR=选项

适用范围：温度 -10°C 到 150°C; 可耐受各种卫生领域介质及工业油品等各种介质，特别适用于油品。

The sealing rubbers we use are in compliance with hygienic and high purity requirements, such as FDA 177.2600; 3-A-18-03; Class II; USP Class VI Chapter 88 GB 4806.11 and so on.

EPDM=Standard

Scope of application: Temperature -10 °C to 130 °C; PH value about 5~9, can tolerate with various media in the health field and industrial chemicals, low cost (recommended)

FKM(Viton)=Option

Scope of application: Temperature -10 °C to 150 °C; can tolerate with various media in the health field, industrial chemicals, oils, etc. and so on.

FFKM=Option

Scope of application: Temperature -30 °C to 250 °C; can tolerate with various media in the health field, industrial chemicals, oils, etc., can cover almost all media, higher cost

HNBR=Option

Scope of application: Temperature -10 °C to 150 °C; can tolerate with various media in the health field, industrial oils, etc., especially suitable for oil products.



DJ-KLX 系列离心泵

DJ-KLX series centrifugal pump



高效率、低噪音、

维护简单经济、高洁净的解决方案

Solution for high efficiency, low noise, simple and economical maintenance, high purity



随着市场需求的变化和技术的发展，我们希望在高洁净泵领域中树立新的技术标准，为此我们借助了流体学软件分析和我们20多年的制造及工程应用的经验，进行一系列的技术升级和优化。

DONJOY DJ-KLX 系列离心泵是基于KS离心泵基础上进行升级，它继承了KS离心泵技术优点，同时优化了内部结构、叶轮设计、死角处理、机封压力平衡设计且机封完全被处在冲洗区域。我们还对泵外部卫生也进行了优化，使其内部更加卫生、外部减少死角，由于没有死角区域，它非常容易被CIP清洗、SIP杀菌等。另外我们对DJ-KLX 系列泵保持了最大的灵活性组合应用，如，泵出口角度可以从 0° – 135° 之间任意调整，泵盖采用手轮螺母，这样对泵维护和保养及机封的更换，保持了高效，降低了人员高度专业性的要求，而这些无需特殊的工具。因而达到了、高效、卫生、高可靠性及低成本的目的，使DJ-KLX 系列离心泵成为一款高性能的泵。



With the change of market demand and the development of technology, we hope to set up new technical standards in the field of high clean pump, for this reason, we have made a series of technology upgrades and optimization with the help of the Fluid science software analysis and our more than 20 years experience in manufacturing and engineering application.

Donjoy DJ-KLX series Centrifugal pump is upgraded from KS centrifugal pump, not only optimize the internal structure, such as impeller design、dead angle treatment、machine seal pressure balance design and the machine seal is completely in the flushing area, but also optimize external sanitation of the pump , which makes its internal absolute sanitation and external reduction of dead Angle. Since there is no dead Angle area, it is easy to be cleaned by CIP and sterilized by SIP. In addition, DJ – KLX series pump, has kept the maximum flexibility of combined applications, for example, the pump outlet angle can be arbitrarily adjusted from 0° to 135 ° , the pump cover adopts hand wheel nut, which keeps high efficiency in the maintenance of the pump and replacement of machine seal, and reduces the highly professional requirements to maintenance personnel without special tools. Therefore, the DJ-KLX series centrifugal pump has achieved the goal of high efficiency, health, high reliability and low cost, making it a high performance pump.

技术参数 Technical Specifications

流量 Flow rate	1m ³ /h-140m ³ /h
扬程 Head	70M
温度 Temperature	-20°C到140°C
功率 Power	0.37KW-30KW
材质 Material	304 /316L,1.431/1.4404,ASME BPE 316L ,1.4435 NB2 Fe≤0.5%
表面处理 Surface treatment	≤ Ra0.8 μ m, ≤ Ra0.6 μ m, ≤ Ra0.4 μ m
机封 Machine seal	单机封、双机封Single seal, double seal, 详见配置单See Configuration Table
进/出口连接 Inlet/Outlet connection	螺纹、卡箍、法兰、无菌法兰 Thread, clamp, flange, Aseptic flange
认证 Certification	3-A-02-10(N.O.1579); MD/06/42-EC (N.O.70521616101-00); FDA 177.2600; USP CLASS-II; EG/VO1935/2004

非常简单的维护、无需专用工具、专业人员
Very simple maintenance, no special tools required,
no professionals required



技术优势

- 维护拆卸和安装时，无需专业人员和专用工具，即可完成。
- 初始使用安装调试时，即使出现短暂反向旋转也不会损坏。
- 叶轮和轴之间是通过键槽连接固定，叶轮和机封动环之间是通过销钉固定，机封静环和泵体之间是通过异形法兰固定。
- 兼容单机封和双机封，只需要更换机封即可实现。

Technical Advantages

- Maintenance disassembly and installation can be completed without professional staff and special tools.
- Initial use of installation debugging, even if a short reverse rotation will not be damaged.
- Impeller and shaft are connected by keyway; impeller and mechanical seal rotating ring are connected by pin; mechanical seal static ring and pump body are connected by special-shaped flange.
- Compatible with single and double machine seal, only need to change machine seal.

DJ-KLX 系列离心泵各种配置

DJ-KLX series centrifugal pump various configurations



螺纹接口
Thread connection



卡箍连接
Clamp connection




由任螺母
Union nut



法兰连接进/出口
Flange connection inlet / outlet



90°0° 倾斜出口
90°0° inclined outlet



90°135° 倾斜出口
90°135° inclined outlet



最低弯头排放接口
Elbow bottom discharge outlet




最低排放接口
Bottom discharge outlet

泵进口/出口连接标准

连接方式：螺纹、卡箍、法兰、无菌法兰、KF、等。
标准：DIN SMS ISO IDF RJT ASME BPE 3A I-line


Pump Inlet/outlet Connection Standard

Connection: Thread, Clamp, Flange, Aseptic flange, KF etc.
Standard: DIN SMS ISO IDF RJT ASME BPE 3A I-line



DJ-KLX 系列离心泵机封设计

DJ-KLX series centrifugal pump mechanical seal design



双机封设计
Double mechanical seal design



单机封设计
Single mechanical seal design

机封系统

DONJOY DJ-KLX 系列离心泵机封，联合欧洲瑞典著名公司合作研发，机封设计具有压力平衡设计、超长使用寿命、极易拆装维护、无需特殊专用工具，卫生洁净符合和认证：欧盟 EHEDG，美国 3-A-02-11，FDA1772600 等高洁净要求。并有丰富的机封配置方案。

Mechanical Seal Features



Donjoy DJ-KLX series centrifugal pump mechanical seal is researched and developed together with European Swedish famous company. The mechanical seal is designed with pressure balance and super long working life, can be disassembled and maintained easily without special tools. The sanitary purity is according to EU EHEDG, USA 3-A-02-11, FDA1772600 and so on. and has lots of configuration.

机封配置 Mechanical Seal Configuration

1)SIC/C/EPDM	标准配置 Standard
2)SIC/C/FKM	
3)SIC/C/HNBR	
4)SIC/SIC/EPDM	
5)SIC/SIC/FKM	选型配置 Optional
6)SIC/SIC/HNBR	
7)TC/TC/EPDM	
8)TC/TC/FKM	
9)TC/TC/HNBR	



注意：以上配置适用于单机封和双机封。
Note: Above configurations are suitable for single and double mechanical seal.

DJ-KLX 系列离心泵 DJ-KLX series centrifugal pump



DJ-KLX 离心泵型号说明

DJ-KLX centrifugal pump model instruction




举例 For example:

DJ-KLX-10-5T-22-1.5KW-380V-50HZ-M-1.5/1.5-S

DJ-KLX 离心泵选型表

DJ-KLX centrifugal pump selection table



型号 Model	功率 Power	流量 Flow rate (m³)	扬程 Head (M)	进口/出口 Inlet&outlet	理论重量 (KG)
DJ-KLX-10	1.1KW	3	22	1.5"/1.5"	30
	1.1KW	5	22		30
	1.5KW	3	22		36
	1.5KW	5	22		36
	1.5KW	8	22		36
	1.5KW	9	22		36
	1.5KW	12	20		36
	1.5KW	15	18		36
	2.2KW				40
	2.2KW	18	16		40

型号 Model	功率 Power	流量 Flow rate (m³)	扬程 Head (M)	进口/出口 Inlet&outlet	理论重量 (KG)
DJ-KLX-20-1	2.2KW	5	36	2"/2"	47
	3.0kw				56
	3.0kw				56
	4.0KW	10	36		61
	4.0KW	15	35		61
	4.0KW	20	33		61
	4.0KW	25	30		61
	5.5KW	30	30		83
	5.5KW	36	22		83
	5.5KW	36	22		83
DJ-KLX20-2	5.5KW	20	40	2"/2"	82
	5.5KW	25	37		82
	5.5KW	30	36		82
	5.5KW	36	32		82
	7.5KW	40	30		86
	7.5KW	45	28		86
DJ-KLX-25	4.0KW	5	50	2.5"/1.5"	61
	5.5KW	10	50		82
	5.5KW	15	48		82
	5.5KW	20	45		82
	5.5KW	10	60		83
	5.5KW	15	55		83
DJ-KLX-30	5.5KW			2.5"/1.5"	83
	5.5KW				87
	7.5KW	20	50		87
	7.5KW	25	45		87
	7.5KW	30	40		87
	7.5KW				87

注意：以上数据图相关尺寸不作为实物最终依据，东正保留对于数据更新权限不再另行通知。

Note: The relevant dimensions of the above data diagrams are not regarded as the final basis of the actual object. DONJOY reserves the right to update the data without further notice.



型号 Model	功率 Power	流量 Flow rate (m³)	扬程 Head (M)	进口/出口 Inlet&outlet	理论重量 (KG)
DJ-KLX-35-1	11KW	10	70	3"/1.5' 3"-2"	152
	11KW	15	65		152
	11KW	20	65		152
	11KW	25	60		152
	11KW	30	60		152
	11KW	35	55		152
	15KW	40	50		165
	15KW	45	50		165
	15KW	50	45		165
	15KW	20	70		165



型号 Model	功率 Power	流量 Flow rate (m³)	扬程 Head (M)	进口/出口 Inlet&outlet	理论重量 (KG)
DJ-KLX-40-1	11KW	45	42	3"/2.5' 4"-3"	148
	11KW	50	42		148
	15KW	60	40		162
	15KW	65	40		162
	15KW	70	38		162
	15KW	80	35		162
	15KW	90	33		162
	18.5KW	100	30		171
	18.5KW	110	28		171
	15KW	50	50		162
DJ-KLX-40-2	15KW	60	48	3"/2.5' 4"-3"	162
	18.5KW	70	47		171
	18.5KW	80	46		171
	22KW	85	45		205
	22KW	90	44		205
	22KW	100	43		205
	22KW	110	40		205
	22KW	120	35		205
	30KW	130	30		263
	30KW	140	20		263

注意：以上数据图相关尺寸不作为实物最终依据，东正保留对于数据更新权限不再另行通知。

Note: The relevant dimensions of the above data diagrams are not regarded as the final basis of the actual object. DONJOY reserves the right to update the data without further notice.

DJ-KLX 系列离心泵数据图

DJ-KLX series centrifugal pump data chart




KLX Series	泵头规格 Pump head dimension				外形安装尺寸 Assembly Dimension						进/出口连接方式 Inlet / outlet connection												
	功率 Power (KW)	进口 Inlet d'/DN	出口 Outlet d'/DN	ΦPB	F	LB	H	HB	HC	W	WA	SMS螺纹连接 Thread connection				INCH卡箍连接 Clamp connection				DIN螺纹连接 Thread connection			
												E	LA	HA	L	E	LA	HA	L	E	LA	HA	L
KLX10	1.1KW	1.5"	1.5"	189	63	240	337	199		250	125	56	171	136	512	49	163.7	129	504.7	56	171	136	517
	1.5-2.2KW	1.5"	1.5"	189	63	240	359	189		260	140	56	171	136	534	49	163.7	129	526.7	56	171	136	539
KLX15	1.5-2.2KW	2"	1.5"	250	95	240	359	189		260	140	48	171	155	534	41	163.7	148	526.7	49	172	155	535
	3KW	2"	1.5"	250	95	300	413	219		320	160	48	151	155	576	41	143.7	148	568.7	49	152	155	577
KLX20- I	2.2KW	2"	2"	250	92	240	362	189		320	140	45	165.5	170	584	38	158.2	163	576.7	46	166.5	171	585
	3KW	2"	2"	250	92	300	416	219		340	160	45	172.5	170	591	38	165	163	574	46	176	171	592
KLX20- II	4KW	2"	2"	250	92	300	421.5	211		380	190	45	175	170	594	38	168	163	587	46	176	171	595
	5.5-7.5KW	2"/2.5"	2"	250	92	330	466	231	94.8	340	216	45	172	170	591	38	160	163	580	46	170.5	171	590
KLX25	4KW	3"	1.5"	328	127.5	300	421.5	211		380	190	60	200.5	194	680	49	189.2	183	668.7	59	199.5	193	679
KLX30	5.5-7.5KW	3"	1.5"	328	127.5	330	466	231		380	216	60	200.5	194	680	49	189.2	183	668.7	59	199.5	193	679
KLX35- I	11-15KW	3"	1.5"	363	131	450	551	260		470	254	76	239.5	229	815	65	228.2	222	803.2	75	238.5	229	814
KLX35- II	15KW	3"	2"	363	131	450	551	260		470	254	76	239.5	229	815	65	228.2	222	803.2	75	238.5	230	814
	18.5KW	3"	2"	363	131	450	551	260		470	254	76	239.5	229	815	65	228.2	222	803.2	75	238.5	230	814
KLX40- I	11-15KW	3"	2.5"	315	105	450	551	260		470	254	73.5	248.5	213.5	823	61.5	237.2	202.5	811.7	73.5	247.5	212.5	822
	18.5KW	3"	2.5"	315	105	450	551	260		470	254	73.5	248.5	213.5	823	61.5	237.2	202.5	812	73.5	247.5	212.5	823
	22KW	3"	2.5"	315	105	515	583	281		510	279	73.5	243.5	213.5	919	61.5	232.2	202.5	907.2	73.5	242.5	212.5	918
	30KW	3"	2.5"	315	105	580	655	301		580	318	73.5	254.5	213.5	965	61.5	243.2	202.5	953.2	73.5	253.5	212.5	964

注意：以上数据图相关尺寸不作为实物最终依据，东正保留对于数据更新权限不再另行通知。

Note: The relevant dimensions of the above data diagrams are not regarded as the final basis of the actual object. DONJOY reserves the right to update the data without further notice.

DJ-KLX 系列离心泵数据图(不带外罩)

DJ-KLX series centrifugal pump data chart (without cover)




KLX 系列 Series	外形安装尺寸 Assembly Dimension												进/出口连接方式 Inlet / outlet connection									
	功率 Power (kW)	进口 Inlet d'/DN	出口 Outlet d'/DN	ΦPB	F	L1	A	B	B'	C	K	H1	H2	SMS螺纹连接 Thread connection			INCH卡箍连接 Clamp connection			DIN螺纹连接 Thread connection		
														E	L2	HA	E	L2	HA	E	L2	HA
KLX10	1.1kW	1.5"	1.5"	189	63	269	125	100	/	50	10	80	192	56	196	136	49	188.7	129	56	196	136
	1.5kW	1.5"	1.5"	189	63	285	140	100	/	56	10	90	217	56	196	136	49	188.7	129	56	196	136
	2.2kW	1.5"	1.5"	189	63	301	140	125	/	56	10	90	217	56	196	136	49	188.7	129	56	196	136
KLX15	1.5kW	2"	1.5"	250	90.5	285	140	100	/	56	10	90	217	48	193	155	41	185.7	148	49	193	155
	2.2kW	2"	1.5"	250	90.5	301	140	125	/	56	10	90	217	48	193	155	41	185.7	148	49	193	155
	3kW	2"	1.5"	250	90.5	316	160	140	/	63	12	100	240	48	193	155	41	185.7	148	49	193	155
KLX20-I KLX20-II	2.2kW	2"	2"	250	85	301	140	125	/	56	10	90	217	45	207	170	38	200	163	46	208	171
	3kW	2"	2"	250	85	316	160	140	/	63	12	100	240	45	207	170	38	200	163	46	208	171
	4kW	2"	2"	250	85	351	190	140	/	70	12	112	252	45	207	170	38	200	163	46	208	171
	5.5-7.5kW	2"/2.5"	2"	250	85	399	216	140	/	89	12	132	301	45	207	170	38	200	163	46	208	171
	4kW	3"	1.5"	328	127.5	351	190	140	/	70	12	112	252	60	201.5	194	49	190.2	183	59	201	193
KLX30	5.5-7.5kW	3"	1.5"	328	127.5	399	216	140	/	89	12	132	301	60	201.5	194	49	190.2	183	59	201	193
KLX35-I	11-15kW	3"	1.5"	363	131	477	254	254	210	108	14.5	160	413	76	282	194	65	270.7	222	75	281	229
KLX35-II	15kW	3"	2"	363	131	477	254	254	210	108	14.5	160	413	76	282	229	65	270.7	222	75	281	66
	18.5kW	3"	2"	363	131	477	254	254	210	108	14.5	160	413	76	282	229	65	270.7	222	75	281	66
KLX40-I KLX40-II	11-15kW	3"	2.5"	315	105	477	254	254	210	108	14.5	160	413	73.5	292	213.5	61.2	280.7	202	73.5	291	213
	18.5kW	3"	2.5"	315	105	477	254	254	210	108	14.5	160	413	73.5	292	213.5	61.2	280.7	202	73.5	291	213
	22kW	3"	2.5"	315	105	573	279	279	241	121	14.5	180	434	73.5	292	213.5	61.2	280.7	202	73.5	291	213
	30kW	3"	2.5"	315	105	618	318	305	267	133	18.5	200	473	73.5	292	213.5	61.2	280.7	202	73.5	291	213

注意：以上数据图相关尺寸不作为实物最终依据，东正保留对于数据更新权限不再另行通知。

Note: The relevant dimensions of the above data diagrams are not regarded as the final basis of the actual object. DONJOY reserves the right to update the data without further notice.

DJ-KLX 系列离心泵曲线图


DJ-KLX series centrifugal pump graph




测试条件：介质清水，温度20°C，叶轮转速2900 R.P.M.
(此曲线图亦适用于电机60Hz, 叶轮转速3600R.P.M) Q-流量(m^3/H),
H-扬程(M), P-功率(KW), η % - 泵效率。

Testing condition: medium water, temperature 20°C, impeller speed 2900 RPM
(This graph also applies to motor 60Hz, impeller speed 3600RPM)
Q-Flow rate (m^3/H), H-head (meter), P-power(KW), η % pump efficiency


KLX-10(Q-H曲线图/Graph)




KLX-15(Q-H曲线图/Graph)




KLX-20-1(Q-H曲线图/Graph)




KLX-20-2(Q-H曲线图/Graph)




KLX-25(Q-H曲线图/Graph)




KLX-30(Q-H曲线图/Graph)




KLX-35-1(Q-H曲线图/Graph)




KLX-35-2(Q-H曲线图/Graph)



KLX-40-1(Q-H曲线图/Graph)



KLX-40-2(Q-H曲线图/Graph)





DONJOY looking forward to your visit! Your telecommunications!



东正科技有限公司 DONJOY TECHNOLOGY CO., LTD

地址: 温州空港新区港富路25号

总机: 0577 8699 0888

传真: 0577 8699 8000

ADD: No.25 Gangfu Road, Konggang
New District, Longwan, Wenzhou, China
TEL: +86 577 8699 0888
FAX: +86 577 8699 8000
E-mail: donjoy@cndonjoy.com

www.cndonjoy.com

法律声明:

目录样册版权归东正所有。如有抄袭，必将追究其法律责任和经济赔偿。

东正已获得国家版权局书刊号。东正诸多产品技术，都具有专利保护。如有抄袭，
必将追究法律责任和经济赔偿。

Legal statement:

Copyright of the catalogue belongs to Donjoy. If there is plagiarism,
it will be investigated for legal responsibility and economic compensation.
Donjoy has been granted publications number by Chinese National Copyright.
Donjoy products and technology are with patent protection.
If there is plagiarism, it will be investigated for legal responsibility
and economic compensation.